

ProTac® 2L-X

DUAL FUEL - LITHIUM ION RECHARGEABLE or 2X CR123 FLASHLIGHT

MARKET

APPLICATIONS: Professional Light - Hardware/Tool, Industrial, Law Enforcement, Security, Automotive, Sporting Goods, Consumer.

DESCRIPTION:

The ProTac® 2L-X is a 500 lumen EDC tactical light and incorporates the versatility to use two battery types; two CR123A batteries or one Streamlight Rechargeable Li Ion cell (see Battery detail below). Multi battery versatility means the user can always use primary disposable cells to power the light if the rechargeable cell is out of power and a charging source is not available. Designed for use in all markets, it features a tactical tail cap switch for momentary or constant on operation, three different user selectable programs and a pocket clip for convenience. The aluminum housing with Type II Military Spec anodizing helps make the light extremely durable and abrasion resistant. Packaged with a removable pocket clip and holster. Available in Black.

CASE MATERIAL:

6000 series machined aircraft aluminum with Type II MIL-Spec anodized finish. Available in Black.

DIMENSIONS:

Length: 5.14 in. (13.0 cm) Head Diameter: 1.06 in. (2.7 cm) Body Diameter: .940 in. (2.4 cm)

WEIGHT:

3.9 oz (111 grams) with 2X CR123 batteries.
4.4 oz (125 grams) with optional Li Ion rechargeable battery. (not included in purchase)

LENS:

Glass lens; gasket sealed.

LIGHT SOURCE:

C4® LED technology, impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT:

See chart. Fully regulated output for consistent lumen performance over the battery life.

ON/OFF:

Multi-function, push-button tactical tail switch. One handed operation of momentary, variable intensity or strobe mode. TEN-TAP® programmable switch allows user selection of one of three different programs: high/strobe/low (factory default), high only, or low/high.

RUN TIME:

See Charts. All runtime claims are to 10% of initial lumen output.

BATTERY:

Two (2) 3 Volt CR123A Lithium batteries, (CR123A batteries have a shelf life of 10 years)
One (1) Streamlight Li Ion 18650 protected cylindrical 3.7V 2600 mAh rechargeable battery that has its own cradle charging system.

FEATURES:


C4® LED technology for extreme brightness.
IPX7 rated design; waterproof to 1 meter for 30 minutes. All openings o-ring sealed.
2 meter impact resistance tested.
LED Solid State Power Regulation provides maximum light output throughout battery life.
TEN-TAP® programmable switch allows user to select one of three different programs.
Anti-roll face cap.
Serialized for positive identification.
Removable pocket clip and Holster

APPROVALS:









 Meets applicable European Community Directives.

WARRANTY:

Streamlight's Limited Lifetime Warranty

OPTIONAL
ACCESSORIES:

Streamlight 18650 Charger Kit (includes two 18650 batteries)

	WITH CR123A BATTERIES			WITH 18650 RECHARGEABLE BATTERY		
	FL 1 STANDARD	HIGH	LOW	FL 1 STANDARD	HIGH	LOW
OUTPUT		500 LUMENS	40 LUMENS		500 LUMENS	40 LUMENS
RUNTIME		2h45m	30h		3h15m	30h
DISTANCE		165m	49m		165m	49m
INTENSITY		6,800cd	600cd		6,800cd	600cd

Strobe Run Time: 3 Hr 15 Min Strobe Run Time: 4.5 Hours

